

# Domestic UV Range



## **Copper Range**

Compact UV system, axial flow 304 polished stainless steel reactor, integral ballast/lamp connector with power on/lamp failure LED indicator. 1/2" MNPT & 3/8" FNPT 'combination' inlet/outlet ports.

SC1, SC2.5 & SC4 units in the range. Flow rates from 0.2 to 0.9 m<sup>3</sup>/hr.



## **Silver 'Basic' Range**

304 polished stainless steel reactor. Water tight controller with 4 segment LED display showing lamp life remaining and total operating time. Audible lamp failure alarm.

S1Q-PA, S2Q-PA, S5Q-PA, S8Q-PA & S12Q-PA units in the range.

Flow rates from 0.4 to 3.4 m<sup>3</sup>/hr.



## **Silver 'Plus' Range**

304 polished stainless steel reactor. Water tight controller with 4 segment LED display showing % UV intensity, lamp life remaining and total operating time. Audible lamp failure alarm. Fused solenoid output (solenoid & connection chord sold separately). 4-20 mA output (required optional 'Y' cable, sold separately)

SSM17, 24, 37 & 39 units in the range. Flow rates from 0.6 to 3.4 m<sup>3</sup>/hr.



## **Platinum 'SP' Range**

Axial flow 304 polished stainless steel reactor, controller with LCD display, UV sensor, lamp life remaining and total operating time, audible lamp failure alarm, Volt free contacts, self diagnosis check & Safety-Loc™ Lamp Connector. High Output (HO) UV lamp.

SP320-HO, SP410-HO, SP600-HO, SP740-HO & SP950-HO in the range.

Flow rates from 4.0 to 11.8 m<sup>3</sup>/hr.

**UVO3 Ltd: Specialist suppliers of UV water disinfection equipment**

Feb '09



**UVO3 Ltd**

Tel: +44 (0)1480 355446

E-mail: sales@uvo3.co.uk

Fax: +44 (0)1480 353487

Web: www.uvo3.co.uk