

Domestic UV Range



Copper Range

Compact UV system, axial flow 304 polished stainless steel reactor, integral ballast/lamp connector with power on/lamp failure LED indicator. 1/2" MNPT & 3/8" FNPT 'combination' inlet/outlet ports.

SC1, SC2.5 & SC4 units in the range. Flow rates from 0.2 to 0.9 m³/hr.



Silver 'Basic' Range

304 polished stainless steel reactor. Water tight controller with 4 segment LED display showing lamp life remaining and total operating time. Audible lamp failure alarm.

S1Q-PA, S2Q-PA, S5Q-PA, S8Q-PA & S12Q-PA units in the range.

Flow rates from 0.4 to 3.4 m³/hr.



Silver 'Plus' Range

304 polished stainless steel reactor. Water tight controller with 4 segment LED display showing % UV intensity, lamp life remaining and total operating time. Audible lamp failure alarm. Fused solenoid output (solenoid & connection chord sold separately). 4-20 mA output (required optional 'Y' cable, sold separately)

SSM17, 24, 37 & 39 units in the range. Flow rates from 0.6 to 3.4 m³/hr.



Platinum 'SP' Range

Axial flow 304 polished stainless steel reactor, controller with LCD display, UV sensor, lamp life remaining and total operating time, audible lamp failure alarm, Volt free contacts, self diagnosis check & Safety-Loc™ Lamp Connector. High Output (HO) UV lamp.

SP320-HO, SP410-HO, SP600-HO, SP740-HO & SP950-HO in the range.

Flow rates from 4.0 to 11.8 m³/hr.

UVO3 Ltd: Specialist suppliers of UV water disinfection equipment

Feb '09



UVO3 Ltd

Tel: +44 (0)1480 355446

E-mail: sales@uvo3.co.uk

Fax: +44 (0)1480 353487

Web: www.uvo3.co.uk